

30ft DNV 2.7-3 Office Container for Ekofisk



Custom-designed and manufactured 30ft DNV 2.7-3 Office Container for offshore installation at Oseberg Øst, build in accordance to NORSOK standards. Fully equipped with office furniture.

General specification:

- Steel module designed and build in accordance with DNV standards
- A60 insulation in the walls, ceiling, floor with A60 windows
- 28 mm NORAC sandwich wall plates
- Rapp Bomek pneumatic sliding door
- 3 mm antistatic and antiskid welded linoleum flooring
- Painted with NORSOK M-501 System 1
- Tare: 6815 kg
- Payload: 550 kg

HVAC:

- Built to comply with Statoil regulations, TR 1562 and applicable NORSOK regulations

Electrical installation:

- Electrical installations built in compliance to Statoil regulations TR3023 and TR 3120 and applicable NORSOK regulations
- Interface connections for computers and office equipment

Fire and gas detection/alarm system:

- 3 x smoke detectors, SIL level 2 (exia)
- Manual Call Points in Exe

Specification

	EXTERNAL DIMENSIONS (mm)			INTERNAL DIMENSIONS (mm)		
	LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT
30ft DNV 2.7-3 Office Container for Ekofisk	10000	2800	3000	9840	2640	2500