

Offshore Pressurized Modules



Uniteam offers Offshore Pressurized Modules designed to hold gases or liquids at different pressures. Units meet various delivery requirements with a range of filling capacities.

Pressurized modules are built according to DNV 2.7-1 and DNV 2.7-2 standards, with A60 fire rated panel and ex-proof apparatus for working in hazardous Zone I/II.

Features:

- Flexible dimension and layout
- Customized
- A60 fire rated
- PLC controlled fire and gas detection
- Suitable for Zone I/II and safe area

Certificate:

- DNV 2.7-1/DNV 2.7-2/EN12079
- NORSOK Z-015
- ATEX, IECEx

Application:

- H2S Shelter
- Workshop
- Operating room
- Laboratory cabin
- Living quarters
- Offices



Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT
12ft Pressurized Module, Type B acc NORSOK Z-015	4700	2300	7000	3657	2438	2960
16ft Pressurized Lab Module, Type B acc NORSOK Z-015	3800	8200	12000	4872	2438	2960
20ft Pressurized Module, Type B acc NORSOK Z-015	6950	8050	15000	6058	2438	2960
30ft Pressurized Module, Type B acc NORSOK Z-015	9550	10450	20000	9125	2438	3335
32ft Pressurized Kitchen Module, Type A acc NORSOK Z-015	8600	9900	18500	9800	3400	3400

Other sizes may be supplied on request.