

Offshore Pump Skid



Uniteam Offshore pump skids are designed, manufactured and certified in accordance with DNV 2.7-1 and DNV 2.7-3, as well as EN 12079. These skids are designed for transport pumps to platform. 2 units of skids fixing on base skid, It can be easily installed and removed fast from base skid. It has specialized spreader frame to sling the modules. The advantage is that can move easily and fast when maintaining pumps or generator.

Certification:

- DNV 2.7-1 and DNV2.7-3 certificate

General specification:

- Skid A for pump;
- Skid B for generator;
- Base skid for shipping skid A, B;
- Separater sling for skid A, B;
- Spreader frame for sling whole module

Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT
Skid A	5000	0	5000	3940	1828	1920
Skid B	4500	0	4500	2580	1828	1920
Base skid	1300	10700	12000	6570	2060	315

Other sizes and configurations may be supplied on request.

Equipment:

- Pump frame/skid: Designed and manufactured in accordance with DNV 2.7-1 & 2.7-3, as well as EN 12079;
- Skid A for pump;
- Skid B for generator;
- Base skid;
- Spreader frame ;
- Sling set for skid A and skis B;