

Offshore Mud Logging



Uniteam Offshore Mud Logging in China are built according to DNV.GL 2.7-1 / DNV GL 2.7-2 / IEC60079-13, The cabin with A60 fire rated decoration and EX approved for use in Zone 1 / Zone 2 area. Pressurized cabin with HVAC system. The cabin included air lock, main room, and equipment room.

General specification:

- Structural code: DNV 2.7-1/EN12079
- Design code: IEC60079-13
- Protection: positive pressurization
- Appropriate for hazardous area: Zone 1 / Zone 2
- A60 rated, conforming to SOLAS, 2009
- Fire and gas control panel
- Operation temperature range: -20°C~ +55°C
- Supply voltage: 380~600Vac 3ph
- Supply frequency: 50/60 Hz
- Operation pressure: 50~75Pa
- HVAC system
- Customized furniture

Certification:

- DNV GL 2.7-1/EN12079
- DNV GL 2.7-2
- IEC60079-13
- ATEX, IECEX

Application:

- H2S Shelter
- Workshop
- Operating/Control Room
- Laboratory Cabin
- Living Quarters
- Office

Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT
20ft Mud Logging	9500	1000	10500	6058	2700	2800
29ft Mud Logging	13500	1500	15000	8900	2700	2800
40ft Mud Logging	17000	1500	18500	12192	2700	2800

Other sizes and configurations may be supplied on request.