

# Offshore Open Top and Half Height Containers



Uniteam Offshore Open Top and Half Height Containers are designed, manufactured and certified in accordance with DNV 2.7-1/2.7-3, as well as EN 12079 and IMO/MSC Circular 860. Products are treated and painted according to the NORSOK M- 501 for the use of products in highly corrosive environments.

Malthus Uniteam has an extensive experience in the production and delivery of cargo containers for offshore use. We deliver products in various sizes and for different purposes.

## Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT
10ft Open Top Container	2850	9150	12000	2991	2438	2591
12ft Open Top Container	3250	10750	14000	3655	2438	2590
14ft Open Top Container	3700	12300	16000	4262	2438	2590
16ft Open Top Container	4100	13900	18000	4874	2438	2590
20ft Open Top Container	4700	15300	20000	6055	2438	2590
	4850	15150	20000	6058	2438	2750
10ft Half Height Open Top Container (door or ramp)	2150	10000	12150	2991	2438	1434
	2250	9900	12150	2991	2438	1434
20ft Half Height Open Top Container	3200	8950	12150	6058	2438	1434

*The above are standard dimensions; other sizes may be supplied on request.*