

Offshore Pressurized Module

DNV 2.7-1 and DNV 2.7-2



Uniteam Offshore Pressurized Modules in China are built according to DNV 2.7-1 and DNV 2.7-2, with A60 fire rated panel and EX approved for use in Zone 1 or Zone 2. Units meet various delivery requirements and can be equipped according to your requirements and used for different purposes.

General specification:

- Structural code: DNV 2.7-1/EN12079
- Design code: DNV 2.7-2
- Protection: positive pressurization
- Appropriate for hazardous area: Zone 1 / Zone 2
- A60 rated, conforming to SOLAS, 2009
- Fire and gas control panel
- Air conditioner with ATEX certificate
- Customized furniture

Certification:

- DNV 2.7-1/EN12079
- DNV 2.7-2
- ATEX, IECEX

Application:

- H₂S Shelter
- Workshop
- Operating/Control Room
- Laboratory Cabin
- Living Quarters
- Office

Specification

	WEIGHT (kg)			EXTERNAL DIMENSIONS (mm)		
	TARE	PAYLOAD	MGW	LENGTH	WIDTH	HEIGHT
10ft Pressurized Module	5500	500	6000	2991	2438	2591
12ft Pressurized Module	7500	1000	8500	3658	2438	2800
14ft Pressurized Module	7500	1000	8500	4060	2438	2800
20ft Pressurized Module	8100	400	8500	6058	2438	2591
20ft Pressurized Module	8700	400	9100	6058	2438	2896

Other sizes and configurations may be supplied on request.